

STEPFOLD PODIUM 3



STEPFOLD PODIUM 3

The new unit offers a platform height of 2m, working height of 4m and incorporates a specially designed inclined ladder to allow safe access to the working platform.

Also included is a unique telescopic gated access frame that allows the operative to enter the platform by reducing the width of the frame, access the platform and close the gate behind them, facing outwards for maximum safety.

The Stepfold Podium 3 is ideal for all site requirements that might include painting and decorating, plastering, alarm installations, ventilation on high ceilings and any other trade jobs that might require a slightly higher reach than the standard podiums can provide.

Suitable for both internal and external applications, the Stepfold Podium 3 is easy to assemble and ready to use within minutes. With a built in folding system whereby the unit can be folded flat, the unit is easy to manoeuvre and transport.

The Stepfold Podium 3 have been a very successful addition to the Euro range products and have been very well received with the hire industry.

Stabilizers are included with every unit.

EURO TOWERS LTD

UK Manufacturer of Aluminium Access Equipment

Tel: +44 (0) 1604 644 774 | Web: www.EuroTowers.co.uk | Email: Sales@eurotowers.co.uk
Euro Towers Ltd, Unit 5, Edgemoad Close, Round Spinney Ind Est, Northampton, NN3 8RG



STEPFOLD PODIUM 3

The Step Fold Podium 3


Assembly Instructions

Ensure all parts are present and are not damaged before assembling

Kit List - Podium 3

- 4 x K548 - 5" Castors
- 1 x SFP3 - Stepfold 3 Podium Base Unit
- 1 x SFSP/3 - Step Platform
- 1 x SFPP/3 - Main Platform
- 1 x SFCL - Stepfold 3 Clip in Ladder
- 2 x SFDB - Stepfold 3 Diagonal Brace
- 2 x SFST/3 - Stepfold 3 Stabilizers

	Stepfold Podium 3
Platform Height	2m
Safe Working Load	150Kg
Dimensions	0.9m x 1.2m
Unit Weight C/W Stabilizers	56Kg



- **STABILIZERS MUST BE USED AT ALL TIMES**
- **THIS UNIT IS SUPPLIED WITH 4 CASTORS AS STANDARD**


Step by step guide



Open the unit on a firm and level base, lock the folding section.



Fit the main platform on the 8th rung as shown.



Ensure that the castors are in the braked position.



Fit a diagonal brace from the 1st to the 4th rung of the podium at the back of the unit.



Repeat this process on the front of the unit in the opposite direction as shown.



Fit the ladder 1 rung below the working platform. Pivot the rung until the hook is facing downwards and clip into place.



Fit the step platform at the base of the unit as shown.



Fit stabilizers on both sides of the unit.



Access the platform using the step platform and ladder, keeping 3 points of contact with the unit at all times.



Once the platform is accessed, extend the gate to its full length and close.



The gate can be extended simply by releasing the ring pull plunger. Once the gate is in the designated place the plunger will automatically lock into place.



Please Note: To remove the ladder, release the bottom catches and turn the hooks towards you. This will enable the top to be removed.

Always work on the podium with the folding gate facing the work area
When leaving the podium, always descend facing the folding gate